

SPECIFICATIONS

OPERATING	POWER INPUT	Universal power adapter (100 - 240 VAC, 50 - 60 Hz)	MECHANICAL	DIMENSIONS	Depth: 7.6 in (193,04 mm) Width: 4.4 in (111,76 mm) Height: 3 in (76,2 mm)
	VOLTAGE	6.0 VDC ± 5%		WEIGHT	14.1 oz (399,72 g)
	CURRENT	900 milliamps, maximum		CABLE LENGTH	6 ft (1,8 m)
	DATA INTERFACE	USB and RS-232		POWER EXTENSION FROM Y-CABLE	4 ft (1,22 m)
ENVIRONMENTAL			CONNECTOR TYPES	RJ-45, RJ-11	
			TEMPERATURE	Operating: 32°F to 104°F (0°C to 40°C) Storage: -4°F to 158°F (-20°C to 70°C)	
			HUMIDITY	Operating: 10% to 90% non condensing Storage: up to 100% non condensing	
			ALTITUDE	Operating: 0-10,000 ft (0-3,048 m) Storage: 0-50,000 ft (0-15,240 m)	

ADD SECURITY. REDUCE FRAUD. ACCELERATE TELLER TRANSACTIONS.



MagTek

20725 S Annalee Ave
Carson CA 90746
p 310-631-8602
f 310-631-3956
www.magtek.com
888-624-8350

Customers First. Quality Always.

REGISTERED TO ISO 9001:2000



magtek.com

IntelliPIN SPT

The IntelliPIN SPT (Swipe and Park Technology) is the latest secure, encrypting PINpad from MagTek. Designed with our new Swipe and Park technology, the IntelliPIN SPT reads magnetic stripe cards and smart cards in a single swipe/insert motion. A "card present" detector ensures the card is retained in the unit during the entire transaction, adding security for you and your consumers.



IntelliPIN SPT



IntelliPIN SPT Benefits

- ▶ Personalize the transaction experience by quickly and securely identifying your consumers
- ▶ Eliminate fraud at the teller window
- ▶ Reduce consumers wait time
- ▶ Improve service
- ▶ Boost consumer satisfaction
- ▶ Increase transaction security

IntelliPIN SPT Features

- ▶ Visa PED and 3DES approved
- ▶ Small footprint
- ▶ Ergonomically designed
- ▶ Reads ISO 7811 and AAMVA standard 3-track cards
- ▶ Reads and writes EMV and ISO 7816 smart cards
- ▶ Single unit supports RS-232 and USB connectivity
- ▶ Auxiliary RS-232 port
- ▶ 128 x 64 graphics backlit LCD display
- ▶ Multiple languages supported
- ▶ 13-key keypad with four soft keys
- ▶ Durable keypad
- ▶ Keypad is optimized to aid visually impaired consumers
- ▶ Card Present Sensor
- ▶ Separate security and application processors
- ▶ TRSM enclosure
- ▶ 3DES and single DES
- ▶ Master/Session and DUKPT key management schemes
- ▶ RSA/PKI for smart card security
- ▶ Supports Windows 98, ME, NT, 2000, XP, 2003
- ▶ Optional privacy shield